

Карманные тестовые термометры

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47


эл.почта: cuo@nt-rt.ru || сайт: <https://cooper-atkins.nt-rt.ru/>

POCKET TEST THERMOMETERS

A pocket test thermometer takes the guesswork out of cooking and assures that a displays, taking the temperatures of food, liquids, and surfaces are an easy task.




Cooper-Atkins' bimetal pocket test thermometers have an external dimple on the little to no drift out of calibration, so are less likely to give variable readings.

- ▶ **PROTECTIVE POCKET SHEATH**
- ▶ **MAGNIFYING LENS FOR EASY VIEWING**



DPS300
Swivel Head Digital Pocket Test



		Bimetal	
			
		1236-17	1246-01C
		Bimetal Pocket Test	Bimetal Pocket Test
Temperature Range:		25° to 125°F	-40° to 180°F (-40° to 80°C)
Accuracy:		±2°F	±2°F (±1°C)
Housing Material:		Stainless Steel	Stainless Steel
Dial Diameter:		1" (25cm)	1" (25 mm)
Stem Diameter:		0.150" (3.0 mm)	0.150" (3.0 mm)
Stem Length:		5" (127 mm)	5" (127 mm)
Lens Material:		Magnifying Polycarbonate	Magnifying Polycarbonate
Antimicrobial Plastic:		-	Yes Sheath Only
Weight:		0.5 oz (14 g)	0.5 oz (14 g)
Regulatory Listings:			
Warranty		1 Year	1 Year

safe temperature has been reached to destroy harmful bacteria. With magnifying lens and crisp dial faces or large LCD stem to indicate the minimum insertion point. Digitals yield a faster response and provide greater overall accuracy with



	1246-02C	1246-03C
	Bimetal Pocket Test	Bimetal Pocket Test
	0° to 220°F (-20° to 100°C)	50° to 550°F (10° to 285°C)
	±2°F (±1°C)	±5°F (±3°C)
	Stainless Steel	Stainless Steel
	1" (25 mm)	1" (25 mm)
	0.150" (3.0 mm)	0.150" (3.0 mm)
	5" (127 mm)	5" (127 mm)
	Magnifying Polycarbonate	Magnifying Polycarbonate
	Yes Sheath Only	Yes Sheath Only
	0.5 oz (14 g)	0.5 oz (14 g)
	1 Year	1 Year

	DPS300	DT300
	Swivel Head Digital	Oval Style Digital
Temperature Range:	-40° to 302°F (-40° to 150°C)	-40° to 302°F (-40° to 150°C)
Accuracy:	±2°F (±1°C)	±2°F (±1°C)
Resolution:	0.1°	0.1°
Response Time:	<18 seconds	<20 seconds
Stem Length:	4.75" (121 mm)	4.625" (117 mm)
Shaft Diameter:	0.150" (3.8 mm)	0.150" (3.8 mm)
Housing:	ABS Plastic	ABS Plastic
Power:	(1) 1.5V #LR44	(1) 1.5V #LR44
Auto Shut-Off:	10 min	-
Display LCD:	0.5" (13 mm)	0.875" (22 mm)
Weight:	1 oz (28 g)	0.5 oz (14 g)
Regulatory Listings::		
Warranty	1 Year	1 Year

-20/100C Pocket Test Thermometer 1246-02C-1



SKU:1246-02C-1

The 1246-02C Bi-Metal Pocket Test features a red protective sheath with anti-microbial additive, adjustment tool and pocket clip. NSF listed.

Features

- Includes red protective sheath with anti-microbial additive, adjustment tool and pocket clip
- Magnifying lens for easy reading
- NSF listed

Specifications

Certifications	NSF
Height [in]	5.5
Height [mm]	140
Housing Material	Stainless Steel
Length [in]	1.063
Length [mm]	27
Net Weight [g]	14
Net Weight [oz]	0.5
Resolution	1 °C increments
Response Time	15 sec
Shaft Length	5" / 127mm
Temperature Accuracy [°C]	±1°C
Temperature Range [°C]	-20°C to 100°C
Warranty Period	Limited 1 Year
Width [in]	1.063
Width [mm]	27

-40 to 180 F Pocket Test Thermometer CT180-51



SKU:CT180-51

1" dial 5" stem with calibration sheath. 12 units packed in self merchandising display box.

Features

- Polycarbonate (magnifying) lens material
- Red copper clip with adjusting wrench

Specifications

Dial Diameter	1" / 2.54cm
Housing Material	Stainless Steel
Net Weight [g]	19.8
Net Weight [oz]	0.7
Shaft Diameter	0.14" / 3.56mm
Shaft Length	5" / 12.7cm
Temperature Accuracy [°F]	±2°F
Temperature Range [°F]	-40°F to 180°F
Warranty Period	Limited 1 Year

-40/180F Pocket Test Thermometer 1246-01-1



SKU:1246-01-1

The 1246-01 Bi-Metal Pocket Test features a red protective sheath with anti-microbial additive, adjustment tool and pocket clip. NSF listed.

Features

- Includes red protective sheath with anti-microbial additive, adjustment tool and pocket clip
- Magnifying lens for easy reading
- NSF listed

Specifications

Certifications	NSF
Height [in]	5.5
Height [mm]	140
Housing Material	Stainless Steel
Length [in]	1.063
Length [mm]	27
Net Weight [g]	14
Net Weight [oz]	0.5
Resolution	2 F° increments
Response Time	15 sec
Shaft Length	5" / 127mm
Temperature Accuracy [°F]	±2°F
Temperature Range [°F]	-40°F to 180°F
Warranty Period	Limited 1 Year
Width [in]	1.063
Width [mm]	27

-40/80C Pocket Test Thermometer 1246-01C-1



SKU:1246-01C-1

The 1246-01C Bi-Metal Pocket Test features a red protective sheath and pocket clip. It is field adjustable.

Features

- Includes red protective sheath and pocket clip
- Magnifying lens for easy reading
- Field adjustable

Specifications

Certifications	NSF
Height [in]	5.5
Height [mm]	140
Housing Material	Stainless Steel
Length [in]	1.063
Length [mm]	27
Net Weight [g]	14
Net Weight [oz]	0.5
Resolution	2 °C increments
Response Time	15 sec
Shaft Length	5" / 127mm
Temperature Accuracy [°C]	±1°C
Temperature Range [°C]	-40°C to 80°C
Warranty Period	Limited 1 Year
Width [in]	1.063
Width [mm]	27

0-220F Pocket Test Thermometer CT220-51



SKU:CT220-51

1" dial 5" stem with calibration sheath. 12 units packed in self merchandising display box.

Features

- Polycarbonate (magnifying) lens material
- Red copper clip with adjusting wrench

Specifications

Dial Diameter	1" / 2.54cm
Housing Material	Stainless Steel
Net Weight [g]	19.8
Net Weight [oz]	0.7
Shaft Diameter	0.14" / 3.56mm
Shaft Length	5" / 12.7cm
Temperature Accuracy [°F]	±2°F
Temperature Range [°F]	0°F to 220°F
Warranty Period	Limited 1 Year

0/220F Pocket Test Thermometer 1246-02-1



SKU:1246-02-1

The 1246-02 Bi-Metal Pocket Test features a red protective sheath with anti-microbial additive, adjustment tool and pocket clip. NSF listed.

Features

- Includes red protective sheath with anti-microbial additive, adjustment tool and pocket clip
- 1" diameter magnifying lens for easy reading
- NSF listed

Specifications

Certifications	NSF
Height [in]	5.5
Height [mm]	140
Housing Material	Stainless Steel
Length [in]	1.063
Length [mm]	27
Net Weight [g]	14
Net Weight [oz]	0.5
Resolution	2 F° increments
Response Time	15 sec
Shaft Length	5" / 127mm
Temperature Accuracy [°F]	±2°F
Temperature Range [°F]	0°F to 200°F
Warranty Period	Limited 1 Year
Width [in]	1.063
Width [mm]	27

10/285C Pocket Test Thermometer 1246-03C-1

SKU:1246-03C-1

The 1246-03 Bi-Metal Pocket Test features a red protective sheath with anti-microbial additive, adjustment tool and pocket clip. NSF listed.

Features

- Includes red protective sheath with anti-microbial additive, adjustment tool and pocket clip
- Magnifying lens for easy reading
- NSF listed

Specifications

Certifications	NSF
Height [in]	5.5
Height [mm]	140
Housing Material	Stainless Steel
Length [in]	1.063
Length [mm]	27
Net Weight [g]	14
Net Weight [oz]	0.5
Resolution	2 °C increments
Shaft Length	5" / 127mm
Temperature Accuracy [°C]	±3°C
Temperature Range [°C]	10°C to 285°C
Warranty Period	Limited 1 Year
Width [in]	1.063
Width [mm]	27

25/125F Pocket Test Thermometer 1236-17-1



SKU:1236-17-1

Pocket Test Thermometer with 1" dial and 5" stainless steel stem. Includes adjustment sheath with anti-microbial additive and pocket clip.

Features

- 5" stainless steel stem
- 1" dial
- Includes adjustment sheath with anti-microbial additive and pocket clip

Specifications

Dimensions – Note	With sheath
Height [in]	5.5
Height [mm]	140
Housing Material	Stainless Steel
Length [in]	1.063
Length [mm]	27
Net Weight [g]	14
Net Weight [oz]	0.5
Resolution	1 F° increments
Response Time	15 sec
Shaft Length	5" / 127mm
Temperature Accuracy [°F]	±2°F
Temperature Range [°F]	25°F to 125°F
Warranty Period	Limited 1 Year
Width [in]	1.063
Width [mm]	27

MAX Digital Pocket Test Thermometer DPP800W



SKU:DPP800W

MAX Digital Pocket Test Thermometer has a Jumbo LCD, 12" reach with pocket sheath and can be used to test dishwasher final rinse cycles. The DPP800W sensor is located at the end of the reduced tip, providing a quick response time of less than 6 seconds. MAX has a large pocket clip with antimicrobial additive and is part of the Accurate for Life Family.

Features

- Quick response time of less than 6 seconds
- Can be used to test dishwasher final rinse cycles
- Large pocket clip with antimicrobial additive
- Jumbo LCD
- NSF listed

Specifications

Battery Life

500 hours (low battery indicator)

Certifications

CE

Height [in]

0.75

Height [mm]

19

Housing Material

FDA approved plastic w/antimicrobial additive

Length [in]

8

Length [mm]

203

Net Weight [g]

28

Net Weight [oz]

1

Resolution

0.1°

Response Time

6 sec

Shaft Length

4" / 102mm

Temperature Accuracy [°C]

±0.5°C from 0°C to 100°C, ±1.0°C from -20°C to 0°C and from

100°C to 150°C, ±1.5°C from -40°C to 20°C

Temperature Accuracy [°F]

±1°F from 32°F to 212°F, ±2°F from -4°F to 32°F and from 212°F

Temperature Range [°C]

to 302°F, ±3°F from -40°F to -4°F

-40°C to 232°C

Temperature Range [°F]

32°F to 120°F steam-filled environment, industrial dishwashers:

180°F, 2 min cycle

-40°F to 450°F

Warranty Period

Lifetime

Waterproof Rating

IPX7 (dishwasher safe)

Width [in]

1

Width [mm]

25

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: cuo@nt-rt.ru || сайт: <https://cooper-atkins.nt-rt.ru/>