

Панельные счётчики

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: cuo@nt-rt.ru || сайт: <https://cooper-atkins.nt-rt.ru/>

PANEL METERS

Easily monitor the internal temperature of your coolers and freezers without use in walk-in refrigerators, display cases, holding and specialty cabinets, dairy

- ▶ **RETRO-FIT APPLICATIONS**
- ▶ **REMOTE INTERIOR TEMPERATURE READINGS**



	DM120	DM120S-0-3
	Front Flange, Back Connect	Back Flange, Back Connect
Temperature Range:	-40° to 120°F (-40° to 48°C)	-40° to 120°F (-40° to 48°C)
Accuracy:	±2°F (±1°C)	±2°F (±1°C)
Resolution:	0.1°	0.1°
Ambient Operating Range:	15° to 150°F up to 90% non-condensing	15° to 150°F up to 90% non-condensing
Response Time:	30 second updates	30 second updates
LCD:	1.3" x 0.5" (33 mm x 13 mm)	1.3" x 0.5" (33 mm x 13 mm)
Lead Length:	39" (1 m)	39" (1 m)
Case Material:	Stainless Steel	Stainless Steel
Case Dimensions:	3.0" x 1.375" (76 mm x 27 mm)	3.47" x 1.1" (88 mm x 28 mm)
Power:	(1) 1.5V #LR754	(1) 1.5V #LR754
Mounting:	Front Flange	Back Flange
Weight:	2.5 oz (71 g)	3.5 oz (999 g)
Regulatory Listings:	CE NSF RoHS	CE NSF RoHS
Warranty:	1 year	1 year

	6142-13
	Front Flange, Back Connect
Temperature Range:	-40° to 120°F (-40 to 50°C)
Accuracy:	±2°F (±1°) at 10° and 40°F (-12° and 4.5°C) ±5°F (±2.5°C) at 110°F (43°C)
Dial Dimension:	2" (51 mm)
Capillary Length:	48" (1.2 m)
Case Material:	Stainless Steel
Flange:	Front
Connection:	Back
Mounting:	Flush
Weight:	5 oz (142 g)
Regulatory Listings:	RoHS
Warranty:	1 year

opening the door. Our NSF-listed panel meters offer an easy solution to reading internal air temperatures perfect for cases, freezers and more.







	6142-06	6142-20 6142-58	6642-06	6812-02	7112-01 7612-06
	Front Flange, Back Connect	Front Flange, Back Connect	Strap Hang, Bottom Connect	Back Flange, Back Connect	Front Flange, Back Connect
	40° to 240°F (10° to 115°C)	-40° to 60°F (-40° to 15°C)	-40° to 60°F (-40° to 15°C)	-40° to 120°F (-40° to 50°C)	-40° to 60°F (-40° to 15°C)
	±2°F (±1°C) from 140° to 210°F (60 to 99°C)	±2°F (±1°C) at 10° to 40°F (-12° to 4.5°C)	±2°F (±1°C) at 10° to 40°F (-12° and 4.5°C)	±2°F (±1°C) at 10° to 40°F (-12° and 4.5°C) ±5°F (±2.5°C) at 110°F (43°C)	±2°F (±1°C) at 10° to 40°F (-12° to 4.5°C)
	2" (51 mm)	2" (51 mm)	2" (51 mm)	2" (51 mm)	2.5" (64 mm)
	48" (1.2 m)	48" (1.2 m) - 6142-20 20' (6.1 m) - 6142-58	48" (1.2 m)	48" (1.2 m)	Strap Hanger (7612-06)
	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
	Front	Front	Strap Hanger no flange	Back	Front - 7112-01 Bottom - 7612-06
	Back	Back	Bottom	Back	Back - 7112-01 -
	Flush	Flush	-	Surface	Flush - 7112-01 -
	5 oz (142 g)	5 oz (142 g)	5 oz (142 g)	5 oz (142 g)	7 oz (198 g) - 7112-01 5.6 oz (159 g) - 7612-06
	RoHS	RoHS	RoHS	RoHS	RoHS
	1 year	1 year	1 year	1 year	1 year

DIGITAL PANEL METERS

Easily monitor the internal temperature of your coolers and freezers without use in walk-in refrigerators, display cases, holding and specialty cabinets, dairy

▶ RETRO-FIT APPLICATIONS ▶ REMOTE INTERIOR TEMPERATURE READINGS



	DM450	PM120-08	PMRH120	SP120
	Front Flange, Back Connect	Mini Rectangular, White	Mini Rectangular, Temp & Humidity	Square Solar Panel
Temperature Range:	-40° to 450°F (-40° to 230°C)	-40° to 122°F (-40° to 50°C)	-12° to 140°F (-24° to 60°C)	-58° to 158°F (-50° to 70°C)
Accuracy:	±2°F (±1°C) from -40° to 300°F ±2% of reading from 301° to 450°F	±1.8°F (±1°C) from -4° to 122°F (-20° to 50°C) ±3.6°F (±2°C) below -4°F (20°C)	±2°F (±1°C) ±5% RH from 30° to 75%RH/ at 32° to 122°F (0° to 50°C)	±2°F (±1°C)
Resolution:	0.1°	0.1°	0.1°/1% RH	0.1°
Ambient Operating Range:	0° to 150°F up to 90% non-condensing	0° to 120°F up to 90% non-condensing	0° to 120°F up to 90% non-condensing	0° to 120°F up to 90% non-condensing
Response Time:	30 seconds 10 second updates	30 seconds	5 seconds	30 seconds 10 second updates
LCD:	1.3" x 0.5" (33 mm x 13 mm)	1.875" x 0.625" (48 mm x 16 mm)	1.875" x 0.625" (48 mm x 16 mm)	1.875" x 0.625" (48 mm x 16 mm)
Lead Length:	39" (1 m)	39" (1 m)	39" (1 m)	10' (3 m)
Case Material:	Stainless Steel	Polycarbonate	Polycarbonate	ABS
Case Dimensions:	3.0" x 1.375" (76 mm x 27 mm)	2.7" x 1.4" x 1.1" (69 mm x 36 mm x 28 mm)	2.75" x 1.5" x 1" (70 mm x 38 mm x 25 mm)	2.75" x 2.75" x .75" (70 mm x 70 mm x 19 mm)
Power:	(1) 1.5V #LR754	(1) 1.5V AA	(1) 1.5V AA	Solar w/ battery back-up (1) 1.5V A76
Mounting:	Front Flange	Optional Mounting Flange (Model 9302)	Optional Mounting Flange (Model 9302)	Hangs
Weight:	3 oz (85 g)	2 oz (57 g)	2.5 oz (71 g)	2.5 oz (71 g)
Regulatory Listings:	CE  RoHS	CE  RoHS	CE  RoHS	CE  RoHS
Warranty:	1 year	1 year	1 year	1 year

opening the door. Our NSF-listed panel meters offer an easy solution to reading internal air temperatures perfect for cases, freezers and more. Our digital panel meters are suitable for a wide range of applications.



SP160
Rectangular Solar
-58° to 158°F (-50° to 70°C)
±1°F (0.5°C) from 32° to 122°F (0 to 50°C) ±2°F from -4° to 32°F (-20° to 50°C) ±3.6°F/2°C <-4°F (-20°C) and > 122°F (50°C)
0.1°
0° to 120°F up to 90% non-condensing
10 second updates
1.4" x 0.5" (36 mm x 13 mm)
48" (1.2 m)
ABS
4.5" x 1.125" x .625" (114 mm x 29 mm x 16 mm)
Solar w/ battery back-up (1) 1.5V AAA
Hangs
3 oz (85 g)
CE RoHS
1 year

	T158	TRH122M	TRH158-0
	Digital w/ Remote Sensor	Mini Thermometer Hygrometer	Min/Max Thermometer Hygrometer
Temperature Range:	(Internal) 32° to 122°F (0° to 50°C) (External) -58° to 158°F (-50° to 70°C)	14° to 122°F (-10° to 50°C)	32° to 122°F (0° to 50°C)
Accuracy:	±2°F (±1°C)	±2°F (±1°C)	±2°F (±1°C) ±5% RH
Humidity:		10% to 99% RH	25% to 90% RH
RH Accuracy:	-	±5% from 25% to 95% RH	±5%
Unit Dimensions:	5" x 1.5" x 3.5" (127 mm x 38mm x 89mm)	2.75" x .75" x 4.25" (17 mm x 19mm x 108mm)	5" x .875" x 3.5" (127 mm x 22mm x 89mm)
Resolution:	-	0.1°	0.1°/1.0%RH
Display - LCD	2.875" x 2.125" (73 mm x 54 mm)	1.5" x 0.5" (38 mm x 13 mm)	2.875" x 2.125" (73 mm x 54 mm)
Power:	(1) 1.5V Battery AAA	(1) 1.5V Battery AAA	(1) 1.5V Battery AAA
Mounting:	Hangs or Stands	Hangs	Hangs or Stands
Weight:	5.5 oz (156 g)	3 oz (85 g)	4.5 oz (127 g)
Regulatory Listings:	CE RoHS	CE RoHS	CE RoHS
Warranty:	1 Year	1 Year	1 Year

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: cuo@nt-rt.ru || сайт: <https://cooper-atkins.nt-rt.ru/>