

Игольчатые зонды

Технические характеристики

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: cuo@nt-rt.ru || сайт: <https://cooper-atkins.nt-rt.ru/>

Screw-in Probe with 1/8in NPT Fitting 1030



SKU:1030

Screw-in thermistor puncture probe.

Specifications

Dimensions – Note	Envelope With cable
Height [in]	4
Height [mm]	102
Length [in]	1.25
Length [mm]	29
Net Weight [g]	48
Net Weight [oz]	1.7
Probe Type	Needle Probes
Response Time	20 sec
Shaft Length	2.5" / 64mm
Temperature Range [°C]	-40°C to 149°C
Temperature Range [°F]	-40°F to 300°F
Warranty Period	Limited 1 Year
Width [in]	0.75
Width [mm]	19

Puncture Probe 1078



SKU:1078

7" thermistor puncture probe with coiled cable.

Specifications

Net Weight [g]	57
Net Weight [oz]	2
Probe Type	Needle Probes
Shaft Length	7" / 178mm
Temperature Range [°C]	-40°C to 149°C
Temperature Range [°F]	-40°F to 300°F
Warranty Period	Limited 1 Year

18in Flexible Veterinary Thermistor Probe w/ 12' PVC Cord 6000



SKU:6000

18" Flexible veterinary thermistor probe with a 12ft PVC cord. Used preferably with the TM99A-V Veterinary Thermistor Instrument.

Specifications

Height [in]	1.5
Height [mm]	38
Length [in]	20
Length [mm]	508
Net Weight [g]	57
Net Weight [oz]	1.5
Probe Type	Air Probe
Response Time	50 sec
Shaft Length	18" / 457mm
Temperature Accuracy [°C]	Accuracy of Probe (Independent of Instrument) $\pm 0.2^{\circ}\text{C}$ from 0°C to 70°C . Typical Accuracy outside above range: $\pm 0.75^{\circ}\text{C}$ from -31.7°C to $< -20^{\circ}\text{C}$, $\pm 0.50^{\circ}\text{C}$ from -20°C to $< 0^{\circ}\text{C}$, $\pm 0.40^{\circ}\text{C}$ from $> 70^{\circ}\text{C}$ to 82.2°C .

Temperature Accuracy [°F]	Accuracy of Probe (Independent of Instrument) $\pm 0.4^{\circ}\text{F}$ from 32°F to 158°F . Typical Accuracy outside above range: $\pm 1.4^{\circ}\text{F}$ from -25°F to $< -4^{\circ}\text{F}$, $\pm 0.9^{\circ}\text{F}$ from -4°F to $< 32^{\circ}\text{F}$, $\pm 0.7^{\circ}\text{F}$ from $> 158^{\circ}\text{F}$ to 180°F .
Temperature Range [°C]	-40°C to 93°C
Temperature Range [°F]	-40°F to 200°F
Warranty Period	Limited 1 Year
Width [in]	2
Width [mm]	51

Plastic Shaft Surface Probe 3010



SKU:3010

Plastic Shaft Probe with Aluminum Tip

Specifications

Dimensions – Note	Envelope With cord
Height [in]	6.5
Height [mm]	165
Length [in]	1.75
Length [mm]	45
Net Weight [g]	57
Net Weight [oz]	2
Probe Type	Needle Probes
Response Time	15 sec
Shaft Length	3" / 76mm
Temperature Accuracy [°C]	Accuracy of Probe (Independent of Instrument): $\pm 0.2^{\circ}\text{C}$ from 0°C to 70°C . Typical Accuracy outside above range: $\pm 0.75^{\circ}\text{C}$ from -31.7 to -2°C , $\pm 0.50^{\circ}\text{C}$ from -20 to $< 0^{\circ}\text{C}$, $\pm 0.40^{\circ}\text{C}$ from > 70 to 82.2°C
Temperature Accuracy [°F]	Accuracy of Probe (Independent of Instrument): $\pm 0.4^{\circ}\text{F}$ from 32°F to 158°F . Typical Accuracy outside above range: $\pm 1.4^{\circ}\text{F}$ from -25 to $< -^{\circ}\text{F}$, $\pm 0.9^{\circ}\text{F}$ from -4 to $< 32^{\circ}\text{F}$, $\pm 0.7^{\circ}\text{F}$ from > 158 to 180°F
Temperature Range [°C]	-40°C to 93°C
Temperature Range [°F]	-40°F to 200°F
Warranty Period	Limited 1 Year
Width [in]	0.625
Width [mm]	16

Meat Packing Puncture Probe 1013



SKU:1013

Heavy-duty needle probe designed with for quick response time.

Specifications

Height [in]	8
Height [mm]	203
Length [in]	2.25
Length [mm]	57
Net Weight [g]	113
Net Weight [oz]	4
Probe Type	Needle Probes
Shaft Length	4" / 102mm
Temperature Range [°C]	-40°C to 149°C
Temperature Range [°F]	-40°F to 300°F
Warranty Period	Limited 1 Year
Width [in]	0.625
Width [mm]	16

Puncture Probe with Heavy Duty Cord 1014



SKU:1014

Heavy-duty thermistor probe designed with an extra long shaft length.

Specifications

Dimensions – Note	Envelope With cord
Height [in]	21
Height [mm]	533
Length [in]	2.25
Length [mm]	57
Net Weight [g]	170
Net Weight [oz]	6
Probe Type	Needle Probes
Shaft Length	17" / 432mm
Temperature Range [°C]	-40°C to 149°C
Temperature Range [°F]	-40°F to 300°F
Warranty Period	Limited 1 Year
Width [in]	0.75
Width [mm]	19

Blunt Tip Veterinary Waterproof Probe 2007



SKU:2007

4" Blunt tip veterinary probe. Waterproof. Used preferably with the TM99A-V Veterinary Thermistor Instrument.

Specifications

Dimensions – Note	Envelope With cord
Height [in]	5
Height [mm]	127
Length [in]	1
Length [mm]	25
Net Weight [g]	57
Net Weight [oz]	2
Probe Type	Needle Probes
Shaft Length	4" / 102mm
Temperature Range [°C]	-40°F to 149°F
Temperature Range [°F]	-40°F to 300°F
Warranty Period	Limited 1 Year
Width [in]	0.625
Width [mm]	16

Blunt Tip Veterinary Probe 1050

SKU:1050

3.5" rigid blunt tip veterinary probe. Used preferably with the TM99A-V Thermistor Instrument.

Specifications

Dimensions – Note	Enveloped With cable
Height [in]	6.75
Height [mm]	171
Length [in]	1.75
Length [mm]	44
Net Weight [g]	57
Net Weight [oz]	2
Probe Type	Needle Probes
Shaft Length	3.5" / 89mm
Temperature Range [°C]	-40°C to 149°C
Temperature Range [°F]	-40°F to 300°F
Warranty Period	Limited 1 Year

Needle Probe 1052



SKU:1052

Standard thermistor needle probe. Can be used in "Pete's Plug" port

Specifications

Dimensions – Note	Enveloped With cable
Height [in]	6.75
Height [mm]	171
Length [in]	1.75
Length [mm]	44
Net Weight [g]	57
Net Weight [oz]	2
Probe Type	Needle Probes
Shaft Length	2.875" / 73mm
Temperature Range [°C]	-40°C to 100°C
Temperature Range [°F]	-40°F to 212°F
Warranty Period	Limited 1 Year

General Purpose Puncture Probe 1075



SKU:1075

General Purpose Puncture Probe used to measure temperatures by insertion or immersion.

Specifications

Dimensions – Note	Envelope With cable
Height [in]	7.125
Height [mm]	181
Length [in]	1.75
Length [mm]	44
Net Weight [g]	57
Net Weight [oz]	2
Probe Type	Needle Probes
Response Time	6 sec
Shaft Length	3.75" / 95mm
Temperature Range [°C]	-40°C to 149°C
Temperature Range [°F]	-40°F to 300°F
Warranty Period	Limited 1 Year

Replacement Probe for use with DTT361-01 Cook n Cool Thermo-Timer 9406



SKU:9406

The probe has a specially designed, Silicone-jacketed thermistor cable that won't fray or allow moisture to penetrate inside.

Specifications

Dimensions – Note	With cord wrapped
Height [in]	7
Height [mm]	178
Length [in]	4
Length [mm]	102
Net Weight [g]	28
Net Weight [oz]	1
Probe Type	Needle Probes
Shaft Length	6.5" / 165mm, 90° bend
Temperature Range [°C]	-31°C to 200°C
Temperature Range [°F]	-25°F to 392°F

По вопросам продаж и поддержки обращайтесь:

Алматы (727)345-47-04
Ангарск (3955)60-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Благовещенск (4162)22-76-07
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Владикавказ (8672)28-90-48
Владимир (4922)49-43-18
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-48
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (3522)50-90-47
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37
Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Саранск (8342)22-96-24
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Сургут (3462)77-98-35
Сыктывкар (8212)25-95-17
Тамбов (4752)50-40-97
Тверь (4822)63-31-35

Тольятти (8482)63-91-07
Томск (3822)98-41-53
Тула (4872)33-79-87
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Улан-Удэ (3012)59-97-51
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Чебоксары (8352)28-53-07
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Чита (3022)38-34-83
Якутск (4112)23-90-97
Ярославль (4852)69-52-93

Россия +7(495)268-04-70

Казахстан +(727)345-47-04

Беларусь +(375)257-127-884

Узбекистан +998(71)205-18-59

Киргизия +996(312)96-26-47

эл.почта: cuo@nt-rt.ru || сайт: <https://cooper-atkins.nt-rt.ru/>